

## Monitoring the air quality in cleanrooms in the nano range, and identifying particle sources with the **testo DiSCmini**.



The cleanest rooms in the world are no longer to be found in hospitals. They are situated in so-called fabs, the production plants in the semi-conductor industry. And there's a good reason for this, since the production structures are getting smaller and smaller. The advantage of this is that the chips require less and less energy and space, at the same performance level. On the other hand, there is the disadvantage

that the production processes are becoming increasingly sensitive. If a grain of dust is the same size as several conductors next to each other, it can easily render the whole chip unusable. With the portable nanoparticle measuring instrument testo DiSCmini, Testo provides chip manufacturers with a valuable support tool for monitoring air quality in the nano range, and for identifying undesired particle sources.



### The challenge.

The production of computer chips has now reached the 14 nm process. This not only signifies another milestone in process technology, but is also in much lower ranges than norms specifying the limit values for air purity in cleanrooms in fabs. In its highest class, the currently valid norm ISO 14644-1 prescribes fewer than 10 particles per m<sup>3</sup> with a diameter of more than 0.1 µm. Smaller particles are neither covered by the regulations, nor recorded by the stationary monitoring instruments. For this reason, the instrumentation needed for monitoring nanoparticles in the production process is often lacking, and apart from this, the emission sources of particles in the nano range can only be localized with great difficulty using the usual instruments.

### The solution.

With the portable instrument testo DiSCmini, cleanrooms can be monitored easily and without complications, even in the nano range. testo DiSCmini records the particle number in a time resolution of 1 second, in the range from 10 to 700 nm, and the mean particle size in the range from 10 to 300 nm, additionally providing the LDSA value, which indicates the influence on the human organism. Thanks to its handy size, the low weight and the patented measurement method which functions without the need for operating materials, the instrument is always ready for use.



The nanoparticle measuring instrument  
testo DiSCmini

With one or several testo DiSCmini, the different measurement points inside and outside a cleanroom can be easily monitored and documented. The high time resolution allows the location of origin of nanoparticles to be detected based on the measured data, even if there are no visible signs such as smoke or steam indicating an emission. The generously sized rechargeable battery is designed for an operating time of up to 8 hours. The measurement data are saved on an SD card as a CSV file, where they can be easily further processed.

### The advantages at a glance.

The portable nanoparticle measuring instrument testo DiSCmini supports semi-conductor manufacturers in all important questions surrounding the topic of nanoparticles:

- Simultaneous measurement of particle number, mean particle size and LDSA, with a time resolution of 1 second
- Mobile operation, without operating materials, unaffected by vibrations and independent of the position of the instrument
- Easy identification of particle sources, easy set-up of measurement grids and long-term measurements

### More information.

For more information on testo DiSCmini and answers to all your questions concerning nanoparticle measurement in semi-conductor production, please contact our experts by phone on +49 (0)7653 681-5062 or by sending an e-mail to [sales-nanoparticle@testo.de](mailto:sales-nanoparticle@testo.de)

Testo SE & Co. KGaA  
Celsiusstrasse 2  
D-79822 Titisee-Neustadt, Germany  
Telephone +49 (0)7653 681-5062  
E-mail [sales-nanoparticle@testo.de](mailto:sales-nanoparticle@testo.de)