


MOUNTING PLATES




SMP-99/94
to mount 96 x 48 mm
size unit in place
of 96 x 96 mm cut-out



SMP-147/94
to mount 96 x 48 mm
size unit in place
of 144 x 72 mm cut-out



SMP-147/73
to mount 72 x 36 mm
size unit in place
of 144 x 72 mm cut-out



SMP-1414/99
to mount 96 x 96 mm
size unit in place
of 144 x 144 mm cut-out

DIN RAIL BRACKETS



SRH-94
TS-35 DIN rail brackets
for 96 x 48 mm case



SRH-99
TS-35 DIN rail brackets
for 96 x 96 mm case



SRH-141
TS-35 DIN rail brackets
for 144 x 144 mm case

SECURITY DOOR WITH LOCK



STD-77
transparent IP 54 door
with lock for 72 x 72 mm case



STD-99
transparent IP 54 door
with lock for 96 x 96 mm case



STD-141
transparent IP 54 door
with lock for 144 x 144 mm case

Transparent door with moulded frame acc. to DIN 43700, lockable with security key. Door and frame are made by injection moulding thus assuring an exact fit, an optimal choice of a material which is very strong and with no risk of corrosion; perfect seal-protective system IP 54 provided by all-round soft rubber sealing the moulding; door does not swing in or out sideways on opening; door-frame and frontframe can be exchanged.



MOUNTING BRACKETS



SPH-07
1 ÷ 7 mm board thickness
brackets (2 pcs)
standard included with device



SPH-45
1 ÷ 45 mm board thickness
brackets (2 pcs)



SPH-05
1 ÷ 5 mm board thickness
brackets (2 pcs)

REMOTE CONTROLLER



SIR-15
InfraRed remote controllers may be used as external programming keyboard for all SIMEX devices equipped with IR receivers and remote programming functions. Pressing of any local IR controller key, causes transmission of it's code to the device. Functions of particular keys depend on devices features.

Power supply voltage: 6V DC - 4 alkaline batteries type LR44
Operation range: from 0,5 to 5 m (depend on programmed device features)

USB MEMORY

MF-8: the mini USB memory stick is incredibly small and stylish flash drive offering **8GB** data storage. Measuring merely 20,6 x 15,5 x 7,0 mm (weight only 3 g), the mini USB drive is ideal for transporting data and fits inside optional lockable door STD-99/141.

UF-8: MultiCon shape **8GB** USB flash drive / give away USB memory.



PORTABLE CASE

Portable case P130

Portable transporting case, made by PELI, with input connectors for mounting **CMC-99**, **CMC-141** or **SRD-99** data recorders. It is useful in applications where there is no possibility of a typical controller / recorder safe installation. Case is very durable, has IP 65 protection class. On the side of the case there are multipin connectors for sensors and interfaces, according to customer needs.



MULTIPRINT MLP-149



MultiPrint MLP-149 for cooperation with **MultiCon** line devices.
Thermal panel printer, giving possibility to communicate with external devices using USB interface. Printer has possibility to print on thermal paper and self-adhesive labels. The user has the possibility of generating print-outs of the current measurements directly where the recorder is installed.

print media: thermal paper and self-adhesive labels
paper width: standardowa 57 mm
communication interface: mini USB
print resolution: 204 DPI



LICENCE KEYS FOR MULTICON LINE

Licence Key to activate recording functions on the Data Logger

- In order to start using data logging functions, you need to enter the above software licence key.
- Each licence key is individual and refers to device serial number.
- Just use "Enter licence key" option in your data logger "Device information" menu.
- Enjoy this powerful data recording functionality!

LKS-99/141
Data logging licence key for MultiCon line

LKT-99/141
Data logging licence key for MultiCon line - 30 days trial version

Licence Key to activate e-mail notifications on the Data Logger

S/N: 3625P1027
Data Logger key:
1C9-80253-115-50651

- In order to start using e-mail notifications functions, you need to enter the above software licence key.
- Each licence key is individual and refers to device serial number.
- Just use "Enter licence key" option in your data logger "Device information" menu.
- Enjoy this powerful e-mail notifications functionality!

ENS-99/141
E-mail notifications licence key for MultiCon line

ENT-99/141
E-mail notifications licence key for MultiCon line - 30 days trial version

Licence Key to activate MultiLevel Access on the Data Logger

- In order to start using MultiLevel Access functions, you need to enter the above software licence key.
- Each licence key is individual and refers to device serial number.
- Just use "Enter licence key" option in your data logger "Device information" menu.
- Enjoy this powerful MultiLevel Access functionality!

MLS-99/141
MultiLevel Access licence key for MultiCon line (USB dongle option only)

MLT-99/141
MultiLevel Access licence key for MultiCon line (USB dongle option only) - 30 days trial version

JUNCTION BOX



SP-4 or SP-6
Load cell junction box for weight meters
Junction box allows for quick and easy connection from 2 up to 6 load cells in multisensor systems, such as tank scales. The large enclosure of the junction box lets you put excess cable of the load cells inside the box (the cable length shortening is not recommended).

